

15SW-H

PowerTraxx 15SW-H is the perfect application for mounting large equipment and aerial devices. Its elongated and widened frame is heavily reinforced, giving it increased stability and a minimum payload capacity of 36,000 lbs. Enabling this size payload capacity is a combination of heavy duty arched solid steel walking beams, solid rubber tires on steel rims, and heavy duty steel hubs and spindles. A 275 hp Cummins® engine, along with hydrostatic drive system, makes for a smooth ride over 40" wide D-dent tracks.



Main Dimensions

| | |
|------------------|------|
| Overall Length | 330" |
| Overall Width | 126" |
| Overall Height | 116" |
| Ground Clearance | 17" |

Weights

| | |
|----------------------------|-------------|
| Basic Vehicle Weight | 29,000 Lbs. |
| Payload Capacity | 36,000 Lbs. |
| Gross Vehicle Weight | 65,000 Lbs. |
| Ground Pressure – Unloaded | 2.12 psi |
| Ground Pressure – Loaded | 4.20 psi |

Engine

| | |
|--------------------|---------------------|
| Type | Cummins QSC, Tier 3 |
| Capacity | 8.3 Litres |
| Horse Power | 275 @ 2200 RPM |
| Electrical System | 12 V |
| Fuel Tank Capacity | 100 US Gal |

Drive System

| | |
|--------------------|---|
| Type | Hydrostatic |
| Location | Front or Rear |
| Pump Drive | Funk, Triple Pad, Series 28000 |
| Hydrostatic Pumps | Sauer 90 Series Variable Displacement |
| Hydrostatic Motors | Sauer 51 Series Two (2) Speed, Variable Displacement |
| Planetaries | Fairfield W12D |
| Speed | 8 mph |
| Drive Sprocket | 14 Tooth, Steel Hub Sprocket Replaceable Urethane |
| Idler Sprocket | 14 Tooth, Steel Hub Sprocket Replaceable Urethane |

Suspension

| | |
|-------------|---|
| Type | Heavy Duty Arched Walking Beams Solid Steel, Urethane Bushings |
| Load Wheels | 825 x 20, Solid Rubber Tire, 3 Piece Steel Rim |

Steering

| | |
|------|---------------------|
| Type | Electronic Joystick |
|------|---------------------|

Tracks

| | |
|-----------------|--------------------------------|
| Type | Rubber With Steel Grousers |
| Belts | 15" x 6 ply, Goodyear Rubber |
| Bars | D-Dent, 40" x 1/2", Heavy Duty |
| Reinforcing Bar | Optional |

Electrics

| | |
|----------------|------------------------------|
| Alternator | 160 Amp |
| Batteries | 2 x 200 Amp Hour, 1125 CCA |
| Starter | 4.8 kW, 12 V |
| Driving Lights | 2 Forward, 2 Rear |
| Other | Back-Up Alarm, Master Switch |

Cabin

| | |
|------------------|--|
| Type | Single Person, Enclosed, ROPS |
| Heater | 44,000 BTU With Adjustable Defrosters |
| Air Conditioning | Optional |
| Other | Sunroof/Escape Hatch, One (1) Seat With Seatbelt Dome Light, Panel Lights |

Instruments

| | |
|--------|--|
| Gauges | Hydrostatic Oil Temp., Voltmeter, Hourmeter, Engine Oil Pressure, Engine Temp., Fuel Level, Tachometer |
|--------|--|

Manuals

| | |
|------|------------------------|
| Type | 2 Parts, 2 Maintenance |
|------|------------------------|

Optional Equipment

| | |
|----------------------|---|
| Cold Weather Package | Steel Flat Track |
| Front Winch | Rubber Covered Flat track Digital Inclinometer |

Other Options Available Upon Request