PT10

PowerTraxx S

DIMENSIONS

 Weight (basic vehicle)
 11,339 kg [25,000 lbs]

 Overall Length (includes extensions)
 7,417 mm [292 in]

 Overall Width
 2,591 mm [102 in]

 Overall Height
 3,175 mm [125 in]

 Ground Clearance
 432 mm [17 in]

OPERATOR CABIN

Enclosed ROPS, ISO 3471

Single occupancy

Seat belt

44,000 BTU heater with defrosters

Front/rear heavy duty wet blade wiper

Hi-backrest, adjustable suspension seat

Escape Hatch above seat

Seat belt

Air Conditioning

Door window, sliding type

"Operator Presence" sensor in seat

CHASSIS

Heavy duty welded tub Front and rear extensions

Drain holes/plugs Access panels (Qty. 4)

CAPACITIES

 Fuel Tank
 303 L
 [80 US Gal]

 Hydrostatic Tank
 170 L
 [45 US Gal]

 Cooling System
 204 L/min
 [53 US Gal]

SUSPENSION

Solid steel walking beam

825 x 20 solid rubber tires (Qty. 8)

Solid steel hubs, oil filled

Heavy duty arched type

3-piece steel rims

Urethane hubcaps with sight glass

TRACKS

Heavy Duty steel D-dent grouser bar

838 mm [33 in] with Reinforcing Bar

305 mm [12 in], 6ply rubber belting

Tensioner Cylinder, grease type

Steel hub sprocket

12, 14 Tooth replaceable urethane segments

CONTROLS

Microprocessor with LCD colour display

Steering parameters / Diagnostics

Electronic Joystick with counter rotate

Hand throttle, foot pedal

ELECTRICAL SYSTEM

12V DC160 Amp alternatorBatteries (Qty. 3)200 AH, 1125 CCA (each)

PERFORMANCE

Payload 11,340 kg [25,000 lbs]
Maximum Speed 16 km/hr [10 mph]
Fording Depth 1,219 mm [48 in]
Turning Radius Zero degrees
Ground Pressure (6in penetration)

Unloaded 0.182 kg/cm² [2.60 psi]
Loaded 0.332 kg/cm² [4.73 psi]

Maximum Gradeability

 Forward/downhill
 60% [31°]

 Sidehill
 40% [22°]

ENGINE

 Cummins QSB 6.7L, 6 cyl
 Turbo diesel, EPA Stage V

 Horsepower @ 2200 rpm
 164 kW [230 hp]

 Torque @ 1500 rpm
 1,152 N-m [850 lb-ft]

HYDRAULICS

Stiebel pump drive (triple pad)

Sauer Danfoss H1B pumps

Auburn Gear Power Wheel drives

Device pump provision on top pad
Sauer Danfoss H1B motors
Auburn Gear Power Wheel drives

STANDARD EQUIPMENT

AM/FM stereo w/ speakers

12V dash power-point, USB port

Block heater

Central greasing bank
Fire extinguisher

Operators/Parts manuals

Webasto heater w/timer

Back-up camera system w/ LCD colour display

44,000 BTU heater with defrosters

2 Forward lights, 2 Rear lights

Central greasing bank

Hydraulic tank warmer

TOUCH SCREEN DISPLAY/INSTRUMENTS

Hydrostatic oil temperatureVoltmeterEngine oil pressureEngine temperatureFuel levelTachometerWarning lightsBuzzers (optional)High/Low speed selectorHigh/Low idle switch

OPTIONAL EQUIPMENT

Hydraulic winch package

Window guard

Side-view camera

Maintenance kit

Other items available upon request

Beacon / Searchlight

Brush guard

Pintle hitch

Blade/plow kit





