RT15

PowerTraxx 5

DIMENSIONS

 Weight (basic vehicle)
 18,144 kg [40,000 lbs]

 Overall Length (includes extensions)
 8,280 mm [326 in]

 Overall Width
 3,200 mm [126 in]

 Overall Height
 3,276 mm [129 in]

 Ground Clearance
 457 mm [18 in]

OPERATOR CABIN

Enclosed ROPS, ISO 3471

Single occupancy

44,000 BTU heater with defrosters

Front/rear heavy duty wet blade wiper
Hi-backrest, adjustable suspension seat

Escape Hatch above seat

Seat belt

Air Conditioning

Door window, sliding type

"Operator Presence" sensor in seat

CHASSIS

Heavy duty welded tub Front and rear extensions
Drain holes/plugs Access panels (Qty. 4)

CAPACITIES

 Fuel Tank
 380 L [100 US Gal]

 Hydrostatic Tank
 208 L [55 US Gal]

 Cooling System
 204 L/min [53 US Gal]

SUSPENSION

Solid steel walking beam Heavy duty arched type
28 in. steel load wheels (Qty. 8) Track roller guides
Solid steel hubs, oil filled Urethane hubcaps with sight glass

TRACKS

900 mm [36 in], continuous rubber track

Auto-tensioning system

Drive sprocket, 4 segments

Idler wheel

CONTROLS

Microprocessor with LCD colour display Steering parameters / Diagnostics Electronic Joystick with counter rotate Hand throttle, foot pedal Back-up camera system w/ LCD colour display Electronic inclinometer

ELECTRICAL SYSTEM

12V DC160 Amp alternatorBatteries (Qty. 3)200 AH, 1125 CCA (each)

PERFORMANCE

Payload 16,330 kg [40,000 lbs]
Maximum Speed 13 km/hr [8 mph]
Fording Depth 1,524 mm [60 in]
Turning Radius Zero degrees
Ground Pressure (6in penetration)

 Unloaded
 0.217 kg/cm²
 [3.10 psi]

 Loaded
 0.418 kg/cm²
 [5.95 psi]

Maximum Gradeability

Forward/downhill 60% [31°]
Sidehill 40% [22°]

ENGINE

 Cummins QSB 6.7L, 6 cyl
 Turbo diesel, EPA Stage V

 Horsepower @ 2200 rpm
 209 kW [280 hp]

 Torque @ 1500 rpm
 1,288 N-m [950 lb-ft]

HYDRAULICS

Stiebel pump drive (triple pad)

Sauer Danfoss H1B pumps

Auburn Gear Power Wheel drives

Device pump provision on top pad
Sauer Danfoss H1B motors
Auburn Gear Power Wheel drives

STANDARD EQUIPMENT

AM/FM stereo w/ speakers

12V dash power-point, USB port

Block heater

Fire extinguisher

Webasto heater w/timer

Back-up camera system w/ LCD colour display

44,000 BTU heater with defrosters

2 Forward lights, 2 Rear lights

Central greasing bank

Operators/Parts manuals

Hydraulic tank warmer

Electronic inclinometer

TOUCH SCREEN DISPLAY/INSTRUMENTS

Hydrostatic oil temperature

Engine oil pressure

Fuel level

Warning lights

High/Low speed selector

Voltmeter

Engine temperature

Tachometer

Buzzers (optional)

High/Low idle switch

OPTIONAL EQUIPMENT

Hydraulic winch packageBeacon / SearchlightWindow guardBrush guardSide-view cameraPintle hitchMaintenance kitBlade/plow kit

Other items available upon request





